

The Next Steps

Building something useful: GUIs and working some real data

Admin

- **At the end of this read chapter 13 in the book.**
 - Particularly beginning at encoding/json on page 327 up to Structured logging on page 344
- **Quizzes starting ??**
- **Project questions?**

Applications

- We have quite a bit of go basics now
- To build a useful application we need what in addition?

Applications

- We have quite a bit of go basics now
- To build a useful application we need what in addition?
 - Data/input
- Where could we get our data?

Applications

- **We have quite a bit of go basics now**
- **To build a useful application we need what in addition?**
 - Data/input
- **Where could we get our data?**
 - User
 - Files (like what?)
 - The internet (give me some common sources)
 - Databases (common examples?)

Applications

- **We have quite a bit of go basics now**
- **To build a useful application we need what in addition?**
 - Data/input
- **Where could we get our data?**
 - User
 - Files (like what?) Excel and text files
 - The internet : Rest APIs, Remote Procedure calls? Others?
 - Databases (common examples: postgres, sqlite, mariaDB)

Data

- **We'll look at other approaches later but for now we will get data from REST apis**
 - Which begs the question – what are REST APIs?
 - Lucky Volunteer?™
 -

Data

- **We'll look at other approaches later but for now we will get data from REST apis**
 - Which begs the question – what are REST APIs?
 - Lucky Volunteer?™
 - Mechanism for letting an application ask a website for data (usually json, sometimes xml)
 - Instead of “scraping” the webpage.

JSON

- **So what is JSON?**
 - Lucky Volunteer?™

JSON

- **So what is JSON?**
 - Text format to send data
 - As JSON objects
 - JSON objects are a lot like what that you have seen earlier in the program?
 - And lists of JSON objects

JSON

- **So what is JSON?**
 - Text format to send data
 - As JSON objects
 - JSON objects are a lot like what that you have seen earlier in the program?
 - Python dictionaries
 - Or
 - Java record classes
 - Which is closer to the way GO uses do you suppose?
 - And lists of JSON objects

JSON

- **So what is JSON?**

- Text format to send data

- As JSON objects

- JSON objects are a lot like what that you have seen earlier in the program?

- Python dictionaries

- Or

- Java record classes

- Which is closer to the way GO uses do you suppose: Closer to the Java approach

- And lists of JSON objects

JSON

• Sample JSON

- From <https://openlibrary.org/dev/docs/api/lists>
- {
- "links": {
- "self": "/people/george08/lists.json",
- "next": "/people/george08/lists.json?limit=5&offset=5"
- },
- "size": 12,
- "entries": [- {
- "url": "/people/george08/lists/OL13L",
- "full_url":
"/people/george08/lists/OL13L/Various_Seeds_for_Testing",
- "name": "Various Seeds for Testing",
- "last_update": "2010-12-21T00:46:17.712513",
- "seed_count": 13,
- "edition_count": 13181
- }
-]
- }

• Sample JSON part II

- {
- "url": "/people/george08/lists/OL97L",
- "full_url":
 - "/people/george08/lists/OL97L/Time_Travel",
- "name": "Time Travel",
- "last_update": "2010-12-17T18:27:14.781336",
- "seed_count": 5,
- "edition_count": 838
- },
- ...
- }}

Getting Data from the web

- **What protocol do we use to get data from the web?**
 - Students who have taken the networks class

Getting Data from the web

- **What protocol do we use to get data from the web?**
 - Students who have taken the networks class
- **http(s) right?**
- **Go go developed in late 2000s so *good* support in the standard library**
 - net/http package
 - Updated fairly recently
 - Returns a response struct and an error
 - <https://golang.org/src/net/http/response.go>
 - Mostly we care about StatusCode
 - And Body

Http package structs and interfaces

- Here are the bits of the http package we need for this kind of task
 - this is the newer way – many LLMs are still suggesting the 2010s way
`http.Client` struct
 - will connect to the server, for now use zero value for all but Timeout
`http.NewRequestWithContext`
 - The 2020s way to create a request struct. Several params needed
`apiClient.Do(request)`
 - You call the `client.Do` function passing the request, returns response and error

Painless JSON in go

- OK well 'painless' is optimistic, but far less painful than it was just 2 years ago.
- **First create the structs that you need for the JSON**
 - This is something that LLMs are really good at
- **Then Use the encoding/json package.**

Let's Try it.

- **We'll start with a fairly straightforward API**
 - The open library API
 - It is free – not even an API key needed (as long as you don't make too many requests per second)
 - Sample query
 - <https://openlibrary.org/search.json?author=zeihan>
 - I've picked an Author that has a limited number of records, but enough interesting going on that we can get the right structs

LLMs

- **Tell me about LLMs – the current hotness in AI**

LLMs

- **Tell me about LLMs – the current hotness in AI**
 - Good:
 - Can often help someone who is really bad at a task look somewhat competent
 - I'm not good at creating images – so I can use AI and manage
 - They are really good doing the small (even if they seem large to students) projects that we do in academia
 - Bad:
 - Often very bad at creating something that has to work in a larger context
 - Often very bad at doing something that requires specialized knowledge.

LLMs and JSON

- LLMs are usually **really good** at limited scope, self contained, well known problems.
 - And that is exactly the kind of problem that building the go structs that will represent the json data is
 - So run the API link that I had in your favorite browser.
 - And copy the resulting json
 - Feed it into your favorite LLM harness and ask it to give you the go structs

LLMs and JSON

- **Normally one would want to double check the code generated by LLMs (if one wanted maintainable software)**
 - Despite what AI company marketing people might say
 - But for this task it almost always gets it right.
- **Big Caveat.**
 - Some JSON APIs have fields that are optional: they exist in some records but not in others.
 - You need to find a json response that has both to get the LLM to generate the right structs

Getting the JSON

- In the examples to follow, know that my LLM called the two structs needed

OpenLibrarySearchResponse

And

Book

- So those are what you see in this exemplar code

What do we need to check for?

- **Whenever we do any of the following, what do we need to check for?**
 - Open a file
 - Read a file
 - Connect to the internet
 - Get data from that internet connection?
- **How are they handled in python and java?**

What do we need to check for?

- **Whenever we do any of the following, what do we need to check for? Errors that aren't programming errors**
 - Open a file
 - Read a file
 - Connect to the internet
 - Get data from that internet connection?
- **How are they handled in python and java?**
 - Exceptions!
 - Go doesn't use exceptions – errors that have to be handled

Example function: let's look and ask questions

```
func getBookData(author string) ([]Book, error) {  
    var result []Book  
    apiClient := &http.Client{  
        Timeout: 30 * time.Second,  
    }  
    fullAddress := fmt.Sprintf("%s%s", ServerAddress, author)  
    request, err := http.NewRequestWithContext(  
        context.Background(),  
        http.MethodGet, fullAddress, nil)  
    if err != nil {  
        return nil, err  
    }  
    response, err := apiClient.Do(request)  
    if err != nil {  
        return nil, err  
    }  
    if response.StatusCode != http.StatusOK {  
        return nil, fmt.Errorf("unexpected status code: %d",  
response.StatusCode)  
    }  
}
```

```
const ServerAddress = "https://openlibrary.org/search.json?author="
```

```
defer response.Body.Close()  
  
var jsonResponse = OpenLibrarySearchResponse{}  
err =  
json.NewDecoder(response.Body).Decode(&jsonResponse)  
if err != nil && err != io.EOF {  
    print("Error the actual response body was: ",  
response.Body, err)  
    return nil, err  
}  
  
result = jsonResponse.Docs  
return result, nil  
}
```

In class exercise

- **Write a main function that will call the function from previous slide**
 - Ask the user for an author
 - Call the `getBookData` function, passing the author from user
 - If there was an error, report the error.
 - If there was not, then print each book struct on its own line.

In class exercise

- **Write a main function that will call the function from previous slide**
 - Ask the user for an author
 - Call the `getBookData` function, passing the author from user
 - If there was an error, report the error.
 - If there was not, then print each book struct on its own line.

GUIs

- **What kind of GUI programming have you done?**
 - Quick survey

GUIs

- **What kind of GUI programming have you done?**
- **My guess before talking with you all**
 - Java: JavaFX, maybe android and swing,
 - Kotlin: android?
 - Swift: iOS native?
 - Python: pyQT or similar?
 - javascript: react, angular etc
 - Anything else?

Threads and event handling

- What are threads and events?
- How do most GUI libraries handle threads and events?

Threads and event handling

- **How do most GUI libraries handle threads and events?**
 - Main thread spawns new thread which will run the GUI, your main thread often becomes vestigial
 - java's main 'method' or
 - python's first method called in the `if __name__ == '__main__':` block
 - How do events get handled?

Threads and event handling

- **How do most GUI libraries handle threads and events?**
 - Main thread spawns new thread which will run the GUI, your main thread often becomes vestigial
 - java's main 'method' or
 - python's first method called in the `if __name__ == '__main__':` block
 - How do events get handled?
 - The GUI library has an event loop, you provide callback functions in your code.
 - Event loop? Callbacks? (let the students answer)

Look, feel and layout?

- **How was the arraignment and look and feel done for GUIs in the 'classical era' of programming?**
 - 1980ish-2010ish?

Look, feel and layout?

- **How was the arraignment and look and feel done for GUIs in the 'classical era' of programming?**
 - 1980ish-2010ish?
 - Put controls on window, use some sort of layout to arrange them. Use static properties to paint them the right way.
 - Best in an era of laptops and desktops – aspect & size doesn't change during run
 - And in current era 2010ish-now ?

Look, feel and layout?

- **How was the arraignment and look and feel done for GUIs in the 'classical era' of programming?**
 - 1980ish-2010ish?
 - Put controls on window, use some sort of layout to arrange them. Use static properties to paint them the right way.
 - Best in an era of laptops and desktops – aspect & size doesn't change during run
 - And in current era 2010ish-now ?
 - Use some sort of layout to arrange them, use CSS to make them look nice.
 - Useful for mobile and multi-monitor era size and aspect ratio might change

GUIs and Go

- **If we look at the awesome go list**
 - Lots of GUI choices
 - <https://github.com/avelino/awesome-go#gui>
 - Three important categories
 - Go wrappers around c/c++ libraries (wxwindows qt etc)
 - Electron wrappers or clones (someone tell me about electron) (wails etc)
 - Pure go implementations (fyne, gio etc)

Fyne

- **I'll use Fyne in this class for GUI**
 - 'materials design' GUI
 - Originally a google standard
 - Designed to have the same application look the same across platforms.
 - For last couple of years, can now compile to webassembly
 - And deploy applications to web.
 - Otherwise classic GUI development feel
 - Official docs <https://fyne.io/>

Hello Fyne

- Here is the official hello world for fyne

```
package main
import (
    "fyne.io/fyne/v2/app"
    "fyne.io/fyne/v2/widget"
)
func main() {
    a := app.New()
    w := a.NewWindow("Hello")
    w.SetContent(widget.NewButton(
        "Click me",
        func() { println("Hello!") },
    ))
    w.ShowAndRun()
}
```

- Create a fyne app
- Create one more more windows
- Add come widgets to the window
- Finally call one of the run or show functions on the main window

Widgets

- **GUI components**
 - Called widgets, controls, or components depending on the library
- **Widgets divided into two groups in docs**
 - Widgets for one piece of data
 - Eg: <https://docs.fyne.io/widget/label/>
 - Widgets for holding aggregate data
 - Eg <https://docs.fyne.io/collection/list/>
 - Let's take a quick look at what is available there

Layouts

- **Use layouts as a way to arrange components on the window**
 - BorderLayout
 - Use this popular layout if you need something to be big (center) and other smaller stuff around it
 - Box layout: (vbox or hbox)
 - Use to build a column or row of components
 - Grid
 - If you are building something like a calculator, a grid of equally sized components
 - AppTabs
 - Tabs at the top (or side) with a large area that will hold its own layouts

Update to main for GUI

- Update to main and new package wide variables

```
func main() {  
    reader := bufio.NewReader(os.Stdin)  
    fmt.Print("What author would you like to search for? ")  
    author, err := reader.ReadString('\n')  
    author = strings.TrimSpace(author)  
    data, err := getBookData(author)  
    if err != nil {  
        fmt.Println("Error:", err)  
        return  
    }  
    gui := *buildBookGUI(data)  
    gui.ShowAndRun()  
}
```

```
var (  
    books      []Book  
    authorsDisplay *widget.Entry  
    languageDisplay *widget.Entry  
    publishDisplay *widget.Entry  
)
```

The BuildBookGUI function

```
func buildBookGUI(bookData []Book) *fyne.Window {
    guiApp := app.New()
    books = bookData
    mainWindow := guiApp.NewWindow("Book GUI")
    directions := widget.NewLabel("Select a book")
    directions.Alignment = fyne.TextAlignCenter
    directions.TextStyle = fyne.TextStyle{Bold: true}
    titleList := widget.NewList(func() int { return len(books) },
        func() fyne.CanvasObject {
            return widget.NewLabel("Placeholder")
        },
        func(i widget.ListItemID, selected fyne.CanvasObject) {
            selected.(*widget.Label).SetText(books[i].Title)
        })
    titleList.OnSelected = bookSelected
    detailsPanel := makeDetailsPanel()
    mainLayout := container.NewBorder(directions, nil, nil, detailsPanel, titleList)
    mainWindow.SetContent(mainLayout)
    mainWindow.Resize(fyne.NewSize(800, 800))
    return &mainWindow
}
```

- Some of this you've seen
 - List gets created with three functions as params
 - First two usually always same,
 - return len of data
 - and create label with default text
 - Then function to actually put correct text
 - After that add OnSelected function
 - Border panel param order
 - (top,bottom, left, right, center)

AddDetailsPanel

```
func makeDetailsPanel() *fyne.Container {  
    <snip>  
    detailsPanel := container.New(layout.NewVBoxLayout())  
    a := widget.NewLabel("Authors displayed below:")  
    authorsPanel.Add(a)  
    authorsDisplay = widget.NewEntry()  
    authorsDisplay.MultiLine = true  
    authorsDisplay.PlaceHolder = "Authors will appear here"  
    authorsDisplay.Resize(fyne.NewSize(200, 100))  
    authorsPanel.Add(authorsDisplay)  
    detailsPanel.Add(authorsPanel)  
    a = widget.NewLabel("Available in these Languages:")  
    languagePanel.Add(a)  
    languageDisplay = widget.NewEntry()  
    languageDisplay.MultiLine = true  
    languageDisplay.PlaceHolder = "Languages will appear here"  
    languageDisplay.Resize(fyne.NewSize(200, 100))  
    languagePanel.Add(languageDisplay)  
    detailsPanel.Add(languagePanel)  
    <snip>  
    return detailsPanel  
}
```

- I cut a third of this, but you can see the general Idea
 - Questions?

OnSelected

```
func bookSelected(i widget.ListItemID) {
    bookAuthors := books[i].AuthorName //AuthorName is a
misnomer, it is a possibly empty list of authors
    if len(bookAuthors) == 0 {
        authorsDisplay.SetText("")
        return
    }
    var authorsNames = strings.Builder{}
    for _, author := range bookAuthors {
        authorsNames.WriteString(author + "\n")
    }
    authorsDisplay.SetText(authorsNames.String())
    pubDate := books[i].FirstPublishYear
    publishDisplay.SetText(strconv.Itoa(pubDate))
    <snip>
}
```

- Once again I cut some of it to get something on the slide
- But setting the languages works a lot like the authors.
- Let's look at the full thing which will be on github
- And ask questions
- And try stuff out.

Display and image

- **Fyne treats images as a widget**

- Can put them in a container like any other widget – then add container to window

```
flagPict := canvas.NewImageFromFile("flag.png")  
flagPict.FillMode = canvas.ImageFillOriginal  
flagPanel := container.NewHBox(flagPict)
```

- There are several NewImageFromXXX methods in the fyne canvas package.
- The fill mode shows display properties
 - Fill original will keep original size and aspect
 - Which could be quite large for some images

Display an image

- You can also use

```
flagPict := canvas.NewImageFromFile("flag.png")
flagPict.SetMinSize(fyne.NewSize(100, 60))
flagPict.FillMode = canvas.ImageFillContain
flagPanel := container.NewHBox(flagPict)
```

- ImageFillContain

- Will keep aspect ratio
- MinSize defaults to (0,0)
- So in side of boderlayout won't be drawn without a new MinSize



**Let's Look at Grad Project 2
ugrad project3**