

Go Routines

Concurrency: The original magic of Go

Admin

- Please read chapter in the Learning Go book for this section.
- Podcast?

Concurrency

- **Someone who has taken Operating Systems**
 - Or done it in real life
 - Remind us what Concurrency is

Concurrency

- **Someone who has taken Operating Systems**
 - Or done it in real life
 - Remind us what Concurrency (in programming) is
 - Break a program/process up in to independent communicating (sub)processes.
 - *May or may not end up being parallel*
 - Depends on hardware and algorithm

Processes and Threads

- **Same group**
 - What are processes and threads?

Processes and Threads

- **Same group**
 - What are processes and threads?
 - Process:
 - the code and data for a running program,
 - in most programs this includes a virtual memory that pretends it is contiguous and starts from memory address 0x0
 - Thread:
 - A 'light weight' process
 - Has its own stack – but shares heap memory

Concurrency

- **Don't over use concurrency in real life**

- Lots of people did in the early days of go
- Just like not everyone is Google <https://programmerfriend.com/not-google/>
- And not everything should be microservices <https://ciarancodes.com/not-everything-needs-to-be-microservices-seriously-stop-it/>
- We don't need everything to be concurrent processes
 - Let's talk a bit about what is a good problem for concurrency and what might not be

Costs

- **Again for the folks who have finished Operating Systems**
 - What is cost of a function call?
 - What is the cost of a 'context switch' (in the operating systems sense)
 -

Costs

- **Again for the folks who have finished Operating Systems**
 - What is cost of a function call?
 - Push stack frame for function
 - Move values from registers to stack and vice versa
 - What is the cost of a 'context switch' (in the operating systems sense)
 - All of the above – and likely adjust the cache to reflect the working memory of the new program
 - Work with new stack for new program

Concurrency Costs

- **Concurrency Costs**
 - Depending on thread model
 - Context switching
 - Some threads being blocked waiting on output from others
 - Cost of communication mechanisms between threads
- **Some of our academic examples will ignore this to keep the examples small**
 - But keep in mind for 'real life'
 - Reference Steve and his tendency to 'try it'

Kernel Threads vs Green Threads

- What is the difference between Kernel Threads and Green threads?

Kernel Threads vs Green Threads

- **What is the difference between Kernel Threads and Green threads?**
 - Kernel threads are managed by the OS
 - Includes context swap (swapping values out of registers.)
 - Green threads are done in user space
 - Emulate OS-threads
 - Can't do parallelism properly
 - Useful for async tasks (Waiting for I/O etc)
 - But no context switch either

Go Routines

- **Go and puns: Go's Threads are called 'Go Routines'**
 - Co-routine pun
- **Go process starts**
 - Go runtime spawns X Kernel threads
 - Then spawns green threads within them
 - Initially with very small stack so that there is very little overhead till you need them
 - Very efficient – 1000 go routines is possible without causing a modern computer to *thrash*
 - Thrash? Lucky Volunteer?

Go routines

- **Turn any function into a go routine by putting the go keyword in front of the call**
 - Pass parameters as usual
 - No return values are possible
 - And go routines don't print to standard output without extra work

```
func main() {  
    for i := 1; i <= 5; i++ {  
        fmt.Println("i =", 100/i)  
    }  
}
```

- If we make `fmt.Println` a go routine nothing printed – let's try

Concurrency Communication Problems

- When we write concurrently, what is the problem

```
package main

import (
    "fmt"
    "os"
    "time"
)

func main() {
    for i := 1; i <= 5; i++ {
        go badWrite("output.txt", fmt.Sprintf("the number for this write is %d", 100/i))
        fmt.Println(fmt.Sprintf("the number for this write is %d", 100/i))
    }
    time.Sleep(10 * time.Second) //sleep to make sure go routines run before program ends.
}

func badWrite(fileName string, text string) {
    file, err := os.OpenFile(fileName, os.O_APPEND|os.O_CREATE|os.O_WRONLY, 0644)
    if err != nil {
        fmt.Println("Error opening file:", err)
    }
    _, err = file.WriteString(fmt.Sprintf("%s\n", text)) //first param is number of bytes written
    if err != nil {
        fmt.Println("Error writing to file:", err)
    }
    file.Close()
}
```

- Let's put this in golang, share on github and try it out.

Traditional solution

- What are the traditional solutions to this 'synchronization' problem?
 - Lucky Volunteer™?

Traditional solution

- **What are the traditional solutions to this 'synchronization' problem?**
 - Mutexes
 - Semaphores
 - monitors/intrinsic locks (used in java)
- **Again post OS people: What happens to a thread that wants to write when the place it need to write to is already busy**
 - With proper synchronization like above?

Traditional solution

- **What are the traditional solutions to this 'synchronization' problem?**
 - Mutexes
 - Semaphores
 - monitors/intrinsic locks (used in java)
- **Again post OS people: What happens to a thread that wants to write when the place it need to write to is already busy**
 - With proper synchronization like above?
 - Sender/writer thread goes to sleep.

Danger of poorly synchronized code

- What does this mean?



Krzysztof Begiedza

@kbegiedza_eu

The plural of "index" is "indices".
The plural of "vertex" is "vertices".
The plural of "mutex" is "deadlock".

Channels

- **The Go solution to inter thread (inter-go routine) communication is a channel**
 - Channels wrap synchronization and data sharing.
 - Possibly buffered

Channels

- **Make a channel – using make of course**

MyChannelVar := `make(chan string)`

- Use make function, first argument is go keyword chan
- Second argument/param is the type of thing you can send on channel
 - Usually common type like int, string etc.
 - But could be arbitrary type

Reading and writing

- **Use the <- operator to read or write from a channel**

- (greater than symbol immediately followed by minus)
- To read from a channel, put this operator to the left of the channel
- Eg:

```
text := <-MyChannelVar
```

- To write to the channel put this operator to the right of the channel
- Eg:

```
MyChannelVar <- "the text here"
```

- Read/write on unbuffered channel twice before inverse puts thread to sleep
- If all threads are sleeping blocked then go panics on deadlock.

Directional channels

- **Make creates a bi-directional channel**
 - But often one function only reads from channel, and one only writes.
 - So make that clear by placing the <- operator next to the chan type when declaring parameters
- ```
func betterWrite(fileName string, receiver <-chan string) {
```
- The above function has a channel parameter that can only be read from
    - Compiler enforced.

# Let's try

- **Let's replace our badWrite with a 'betterWrite' that will use channels to make sure the data ends up in the file in the right order.**
  - We'll
    - take our existing main function
      - create/make a channel
      - Call the new function below as a go routine, passing the channel and a new filename
      - Write the data to the channel after calling the go routine in our loop
    - Make a new function that has the signature of the betterWrite from previous slide
      - Do mostly the same as the badWrite, but get the text to write to the file from the channel

# For-Range and channels

- Often, rather than many goroutines listening to a channel
    - Like we did in our last example
  - Will have one go routine that keeps listening to a channel as long as it is open.
- ```
for text:= range receiver{
```
- Will read from the receiver channel until that channel is closed

Closing channels

- If we read till closed – need close

Closing channels

- **If we read till closed – need close**

`close(MyChannelVar)`

- Most channels are written to from one thread and read from another
- The writer should close the channel
- Once channel is closed
 - Read will give zero value and be fine
 - Use `ok` version to see if value is sent zero val or created

`text, ok := <-receiver`

- Write to closed channel will *panic*. (see chart on page 293)

Select and channels

- **Select for channels**
 - looks a bit like switch
 - But no {} needed for cases
- **Use to read from one of several channels**
 - Which ever has values available
 - If multiple cases possible, go randomly selects.

```
func spawn() {  
    result := 0  
    channel1 := make(chan int)  
    channel2 := make(chan int)  
    channel3 := make(chan int)  
    go calculator(channel1)  
    go calculator(channel2)  
    go calculator(channel3)  
    select {  
    case partialResult := <-channel1:  
        result += partialResult  
        fmt.Println("Partial result from channel 1:",  
partialResult)  
    case partialresult2 := <-channel2:  
        result += partialresult2  
    case partial3 := <-channel3:  
        result += partial3  
        fmt.Println("Partial result from channel 3:", partial3)  
    }  
}
```

Select and Channels II

- Often want to repeat checking the select

- But make sure you have a *break* or *waitgroup* (deferred)
- Which I don't have here

```
func spawn() {  
    result := 0  
    <snip>  
    for {  
        select {  
        case partialResult := <-channel1:  
            result += partialResult  
            fmt.Println("Partial result from channel 1:",  
partialResult)  
        case partialresult2 := <-channel2:  
            result += partialresult2  
        case partial3 := <-channel3:  
            result += partial3  
            fmt.Println("Partial result from channel 3:", partial3)  
        }  
    }  
}
```

WaitGroups

- **When one go routine needs to wait for multiple others to finish**
 - Could close channels in each go routine
 - But if we want to keep them open can use waitgroups.
 - `sync.WaitGroup`
 - Important functions
 - Add
 - Done
 - Wait

WaitGroups II

- **Add**
 - Increments the wait counter
- **Done**
 - Decrements the wait counter
- **Wait**
 - Blocks the thread till the wait counter is 0 again
- **Example from**
 - <https://oneuptime.com/blog/post/2026-01-23-go-waitgroup/view>

```
func main() {  
    var wg sync.WaitGroup  
  
    for i := 1; i <= 3; i++ {  
        wg.Add(1) // Increment counter before goroutine  
  
        go func(id int) {  
            defer wg.Done() // Decrement when done  
  
            fmt.Printf("Worker %d starting\n", id)  
            time.Sleep(time.Second)  
            fmt.Printf("Worker %d done\n", id)  
        }(i)  
    }  
  
    wg.Wait() // Block until counter is zero  
    fmt.Println("All workers completed")  
}
```

Mutex

- **Go does provide a traditional mutex**
 - As per chapter 12 in book
 - Usually use channels
 - Occasionally for many processes checking shared value but not consuming it mutexes the right thing

Reading

- **Chapter 12 in your book of course**
- **Some other links I used**
 - <https://go101.org/article/channel.html>
 - <https://go.dev/tour/concurrency/1>
 - <https://gobyexample.com/channels>
 - The latter two are slides, you want to follow links to the next few.



Reminder: read chapter 12